



PAN-PIONEER Co., Ltd.
民鋒股份有限公司
SPECIFICATION



Name: 1250mm 50P Drum Twist Type Unit Stranding Machine

1.] Main specification:

1.1.) Features:

- 1.1.1.) Type of machine: drum twist type non-backtwist
- 1.1.2.) Purpose: 50P telephone cables unit stranding
- 1.1.3.) Take-up bobbin: 1250mm Max.
- 1.1.4.) Pay-off bobbin: 500mm Max.
- 1.1.5.) No. of pay-off bobbin: 52 pcs.
- 1.1.6.) Finished cable dia: 25mm Max.
- 1.1.7.) Take up rotor speed: 250RPM Max.
- 1.1.8.) "CCCS" central computer control system.
- 1.1.9.) Driven motor: HP AC motor for machine driven
HP AC motor for take up drum



1.2.) Machine composition:

- 1.2.1.) 500mm pay-off stand 52 sets
- 1.2.2.) Guide roller stand..... 2 sets
- 1.2.3.) 5 Heads Sub-unit oscillating..... 1 set (option)
- 1.2.4.) Die plate & stand..... 3 sets
- 1.2.5.) PE tape binding head..... 3 sets
- 1.2.6.) 400mm tapping head 1 set (option)
- 1.2.7.) 600mm rotation wheel capstan 1 set
- 1.2.8.) 1250mm drum twist take up 1 set
- 1.2.9.) "CCCS" operation panel..... 1 set

1.3.) Remarks:

- 1.3.1.) Operation direction: Right hand (from left to right)
- 1.3.2.) If the above specification differs from that of the quotation or sales contract,
according to the quotation or sales contract.



PAN-PIONEER Co., Ltd.
民鋒股份有限公司
SPECIFICATION

ISO 9001 : 2000



EQAICC-Q-R3276

