



# PAN-PIONEER Co., Ltd.

民鋒股份有限公司

## Specification

ITEM	DESCRIPTION	Q'ty	UNIT PRICE	AMOUNT (USD)
------	-------------	------	------------	--------------

### 1. 70 / 75 mm PVC/PE Wire Insulation Line with computerized control system.

#### 1.] Main specification:

- 1.1.) Application: PVC/PE/XLPE wire insulation
- 1.2.) Screw Data: 70/75 mm/OD L/D=26 Variable BM dual thread type
- 1.3.) Output capacity: kg/hr max.(soft PVC)
- 1.4.) Conductor dia.: 2.0 -12.0mm
- 1.5.) Finishing dia: 3.0 - 15.0mm
- 1.6.) X-head: 20mm adjustable centering crosshead.
- 1.7.) Pay off stand: 630mm shaft type.
- 1.8.) Take up stand: 630mm shaftless type.
- 1.9.) Driven motor:
  - 1.9.1.) For extruder: HP AC motor + Inverter.
  - 1.9.2.) For capstan: HP AC motor + Vector Inverter.
  - 1.9.3.) For take-up: HP AC motor + Inverter.
  - 1.9.4.) For 500mm auto coiler: HP AC motor + Inverter.
- 1.10.) Temperature controller: digital type temperature gauge.  
(computer control plus usd3000 as an option)

#### 2.] Machine composition:

- 2.1.) 1250mm cantilever type payoff stand.....1 set
- 2.2.) Wire vibration absorb wheel stand .....1 set
- 2.3.) Wire straightener .....1 set
- 2.4.) 70mm Extruder .....1 set
- 2.5.) Touch Screen temperature control .....1 set(optional)
- 2.6.) Hopper dryer and auto-loader .....1 set
- 2.7.) Ink type Printing device .....1 set
- 2.8.) Water cooling trough .....1 set
- 2.9.) Spark tester .....1 set
- 2.10.) 600mm Dual Wheel capstan .....1 set
- 2.11.) Operation s/control panel .....1 set
- 2.12.) 1250 cantilever type takeup stand.....1 set
- 2.13.) adjustable centering crosshead.....1 set
- 2.14.) Computerized control system(CCCS) .....1 set(optional)

#### 3.] Operation direction: Right hand (from left to right)

1/2

No.50 Lane 573 Ping-Dong Rd., Ping-Zhen City , Tao-Yuan County , TAIWAN , R.O.C.

Tel : +886-3-4604789 Fax : +886-3-4604788

E\_mail : [sales@pan-pioneer.com](mailto:sales@pan-pioneer.com) [Http://www.pan-pioneer.com](http://www.pan-pioneer.com)

表單編號: FM-012-1



70/90/100mm Extrusion Line with Computer Control